

ALMETAL

Self-propelled hay chopper

Benefits

Versatile: it can work with loose hay or straw.

Its 68-knife rotor produces a clean, precise chop.

Maximum stability and optimal maneuverability thanks to the wide handlebar.

 \checkmark

Low maintenance.

Full speed control by the operator thanks to its throttle control and its powered drive wheels make running the unit effortless.

For efficient, low-effort chopping and spreading of straw and hay

Features

13 HP Honda motor with electric starter

48" (122 cm) tub diameter

Grate for standard chop lengths

ALMETAL

Constant.

Options & accessories

ALMETAL

// Fine cut grate

// Conical extension for extra capacity

Standard or Flotrac

This self-propelled bedding chopper is available in a standard or Flotrac model. Both offer the same advantages, while the Flotrac model also includes flotation tires and a steerable rear tire for use in rougher terrain.



Large capacity tub

The large capacity tub means fewer trips to the filling station. Its all-steel monocoque design eliminates risk of drive hoop breakage. It is also equipped with a longlasting UHMW bottom seal.



Easy spreading

The two adjustable flaps located at the exit of the chopper allow you to set the desired ejection distance. With a range of up to 17' (5 m), you can quickly distribute the bedding your animals need for their comfort.



Heavy-duty steel rotor

The pre-assembled knife sets on smooth spacer discs making replacement or reversing quick and easy. The spiral knife rotor shaft ensures smooth operation and consistent bedding flow with less horsepower, while reversible mounting reduces maintenance costs.

Specifications



Flotation wheels - Flotrac

The three large tractor-type, low-pressure tires provide great traction in all conditions, and the powerful hydrostatic pump easily handles heavy loads.

Standard self- propelled	Flotrac self- propelled	Stationary*	Gas	PTO driven
48" (122 cm) Ø	48" (122 cm) Ø	48" (122 cm) Ø	28" (71 cm) Ø	48" (122 cm) Ø
51 1/2" (131 cm)	52 1/4" (133 cm)	50" (127 cm)	43 1/4" (110 cm)	51" (129.5 cm)
62" (157.5 cm)	63" (160 cm)	62 1/2" (159 cm)	65 1/2" (166 cm)	54 1/2" (138 cm)
90" (229 cm)	105" (267 cm)	75 3/4" (192 cm)	62 1/2" (159 cm)	75" (190.5 cm)
850 lb (385.5 kg)	1,065 lb (483 kg)	800 lb (363 kg)	585 lb (265 kg)	690 lb (313 kg)
13 HP	13 HP	7.5 HP or 10 HP	9 HP, 11 HP or 13 HP	20 HP minimum - 540 RPM
Traction - Turf type (16 X 7.5)	Flotation - Tractor type	N/A	4.80/4.00-8	N/A
	propelled 48" (122 cm) Ø 51 1/2" (131 cm) 62" (157.5 cm) 90" (229 cm) 850 lb (385.5 kg) 13 HP Traction - Turf	propelled propelled 48" (122 cm) Ø 48" (122 cm) Ø 51 1/2" (131 cm) 52 1/4" (133 cm) 62" (157.5 cm) 63" (160 cm) 90" (229 cm) 105" (267 cm) 850 lb (385.5 kg) 1,065 lb (483 kg) 13 HP 13 HP Traction - Turf Flotation - Tractor	propelled propelled Stationary* 48" (122 cm) Ø 48" (122 cm) Ø 48" (122 cm) Ø 51 1/2" (131 cm) 52 1/4" (133 cm) 50" (127 cm) 62" (157.5 cm) 63" (160 cm) 62 1/2" (159 cm) 90" (229 cm) 105" (267 cm) 75 3/4" (192 cm) 850 lb (385.5 kg) 1,065 lb (483 kg) 800 lb (363 kg) 13 HP 13 HP 7.5 HP or 10 HP Traction - Turf Flotation - Tractor N/A	propelled propelled Stationary* Gas 48" (122 cm) Ø 48" (122 cm) Ø 48" (122 cm) Ø 28" (71 cm) Ø 51 1/2" (131 cm) 52 1/4" (133 cm) 50" (127 cm) 43 1/4" (110 cm) 62" (157.5 cm) 63" (160 cm) 62 1/2" (159 cm) 65 1/2" (166 cm) 90" (229 cm) 105" (267 cm) 75 3/4" (192 cm) 62 1/2" (159 cm) 850 lb (385.5 kg) 1,065 lb (483 kg) 800 lb (363 kg) 585 lb (265 kg) 13 HP 13 HP 7.5 HP or 10 HP 9 HP, 11 HP or 13 HP Traction - Turf Flotation - Tractor N/A 4 80/4 00-8

* A stationary model with a 28" (71 cm) Ø tub is also available.

Specifications, descriptions and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without prior notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.

valmetal.com