

Maxx-Trac Dura-Tech

Less time spent travelling and more loads per day.

- ✓ Steering needs no operator input
- ✓ Easy-to-maintain
- ✓ Has plenty of stopping power for the biggest loads
- ✓ Low load per axle even on the biggest models
- ✓ Can unload in record time
- ✓ Steering reduces tire wear, reduces strain on axles, and reduces damages to roads or fields

4, 6 & 8 wheel spreaders

Features

1/4" Steel tank body (complete body)

1/4" Steel anti-surge baffles

32" Square fill hatch

LED signal light kit

Independent undercarriage

Hydraulic suspension

Mechanical linkage Steering

STOP GETTING PUSHED AROUND.

Auto-steering, all the time.



- ✓ Non-steerable tankers tear up the headlands and roads while Maxx-Trac tankers roll smoothly through corners.
- ✓ Fully automatic steering operates at any speed.



Hubs and spindles (4-3/8") 20,000 LBS

Ready to receive industrial brakes on 2, 4 or 6 wheels

DOT reflective strips on sides and back

Safety chain

Grease lines

Specifications

	TANDEM / 4-WHEEL				TRIDEM / 6-WHEEL				QUAD / 8-WHEEL		
TANKER DIMENSIONS	4000	4500	5000	5700	5600	6200	6600	7400	8500	9600	10200
TANK LENGTH	16 FT	16 FT	20 FT	20 FT	22 FT	22 FT	26 FT	26 FT	34 FT	34 FT	36 FT
TANK PROFILE	LOW	STD	LOW	STD	LOW	STD	LOW	STD	LOW	STD	STD
US GALLONS	4,000	4,500	5,000	5,700	5,600	6,200	6,600	7,400	8,500	9,600	10,200
IMP GALLONS	3,300	3,800	4,200	4,800	4,600	5,200	5,500	6,200	7,100	8,000	8,500
LITERS	15,100	17,200	18,900	21,500	21,200	23,600	2500	2800	32,200	36,300	38,600
OVERALL LENGTH	23 FT	23 FT	27 FT	27 FT	29 FT	29 FT	33 FT	33 FT	41 FT	41 FT	43 FT
EMPTY WEIGHT (LBS)*	14,000	14,250	15,270	15,550	19,330	19,650	20,890	21,130	27,250	27,720	28,580
APPROX LOADED WT.*	47,000	52,250	57,270	63,350	65,330	71,650	75,900	82,700	88,250	107,550	113,100

*Equipped with 850/50x30.5 tires, other tires may weigh less

Trailer options

- Oil-filled hubs
- Auto-greasing
- Ball hitch
- Hydraulic or air brakes
- Weight transfer
- Injector lift kit
- Work lights
- Night travel lighting
- Stainless steel fenders

Tank options

- Stainless steel tank
- 8" discharge
- In-tank agitation
- Sand auger
- Rock trap
- PTO or hydraulic impeller drive
- AR-steel impeller
- Anti-siphon pipe
- Ready for flowmeter kit
- Self-loading kit
- Rear bumper
- Rear hitch
- Hopper
- Hydraulic-door hopper
- Roof-top fill flag
- Low-spray or double-spray discharge
- Transfer arm



Specifications, descriptions and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without prior notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.